



3D Step-file available on request

Signalleuchten mit Reflektor
für enge Reihenmontage

Voyants lumineux avec réflecteur
pour montage rapproché



154S21R301B

158111010G301B

Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires		Length / Länge / Longueur (cm)	Light source Lichtquelle Source lum.		Resistor Widerstand Résistance	
Terminals Anschlüsse Raccords	Surface Oberfläche Surface	Nut Mutter Ecrou				LED 3 mm		Code	V
153 LED terminals LED-Anschlüsse Fils des LED's	B Brass, blackened Messing, geschwärzt Laiton, noircie S Brass, nickel plated Messing, vernickelt Laiton, nickelée	1 2	1 1			Y33U 4200 mcd Yellow Gelb Jaune	0 without ohne sans		
						Y30U 1200 mcd Y301 30 mcd			
154 Solder lugs Lötösen Contact à souder						B71G 6220 mcd B41G 1160 mcd Blue Blau Bleue			
							G41N 17600 mcd G51N 10320 mcd G301 40 mcd Green Grün Verte		
						R33U 4000 mcd R30U 1500 mcd R301 8 mcd Red Rot Rouge			
						W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd White Weiss Blanche			
158 Stranded wire Litze Fil multi-brins	1 Brass, blackened Messing, geschwärzt Laiton, noircie 2 Brass, nickel plated Messing, vernickelt Laiton, nickelée	1 2	1 1		010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	RG36 common cathode only series 153 158 for 24V only 15mA for 28V only 14mA Red-Green Rot-Grün Rouge-Verte			

Sloan_01_GK_Indicator-Lights_19A

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

