

Indicator lights with reflector

Rotation-proof
Option: waterproof IP64 / IP67 / IP68


Signalleuchten mit Reflektor

Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur

Anti-rotation
Option: étanche IP64 / IP67 / IP68

Series 353 / 354 / 358



3D Step-file
available on request



3548S1R521B

358811010Y501B

Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Light source Lichtquelle Source lum.	Resistor Widerstand Résistance	
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface		LED 5 mm	Code	V mA
353 LED terminals LED-Anschlüsse Fils des LED's	4 IP 64 7 IP 67 8 IP 68	B Brass, blackened Messing, geschwärzt Laiton, noircie	1	Y54U 7000 mcd Y50U 3000 mcd Y501 80 mcd B91G 9000 mcd B21G 2120 mcd B61G 1160 mcd G81N 32500 mcd G71N 5620 mcd G501 80 mcd R54U 7000 mcd R50U 3000 mcd R521 80 mcd W55N 22000 mcd W50N 2320 mcd RGWW common cathode RGVW common anode only series 353, 358	0 without ohne sans A 5 20 B 12 20 D 24 20 E 28 20 CL 9-48 20 constant current driver only for Series 354, 358 and only for single colour CL1 5-28 20 constant current driver only for Series 354, 358 and only for single colour	
		S Brass, nickel plated Messing, vernickelt Laiton, nickelée				5 Stainless steel 1.4305 Edelstahl 1.4305 Acier in- oxydable 1.4305
		5 Stainless steel Edelstahl Acier inoxydable	6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie			
		9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **				9
354 Faston 2.8 x 0.5	4 IP 64 7 IP 67 8 IP 68	1 Brass, blackened Messing, geschwärzt Laiton, noircie	1	010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	Z 230 5 only for Series 358*	
		2 Brass, nickel plated Messing, vernickelt Laiton, nickelée				5 Stainless steel 1.4305 Edelstahl 1.4305 Acier in- oxydable 1.4305
		5 Stainless steel Edelstahl Acier inoxydable	6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie			
		9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **				9
358 Stranded wire Litze Fil multi-brins	4 IP 64 7 IP 67 8 IP 68	1 Brass, blackened Messing, geschwärzt Laiton, noircie	1	010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	Z 230 5 only for Series 358*	
		2 Brass, nickel plated Messing, vernickelt Laiton, nickelée				5 Stainless steel 1.4305 Edelstahl 1.4305 Acier in- oxydable 1.4305
		5 Stainless steel Edelstahl Acier inoxydable	6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie			
		9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **				9

Operating Temperature: -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature: -30° to +65°

different LED's of the SLOAN range can be built in

RoHS compliant / ** except surface option 9 (none RoHS)

*refer to installation instructions for 230V version in chapter „F“

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques



Sloan_01_GK_Indicator-Lights_19A