

12V Flexiprint silicone IP64

Standard bright (PLCC2)

Specifications

Voltage	12V
Current	2A
Wattage	4.8W/m
Number of LED's	300pcs
Length of stripe	5m
Operating temperature	-15°~+40°C
Storage temperature	-25°~+60°C
Viewing angle	110°
CE/RoHS compliant	



Benefits


Adhesive tape on backside
IP64 protection

Electrical and optical characteristics (Ta=25°C)

Part number	Colour	Wavelength / CCT	Intensity lm (typ.)	EEC
FPL-B04B-500	blue	472nm	110	E
FPL-G04B-500	green	525nm	480	C
FPL-H04B-500	warm-white	2600-2800°K	2100	A
FPL-N04B-500	warm-white	2800-3100°K	2100	A
FPL-R04B-500	red	639nm	240	E
FPL-S04B-500	natural-white	3800-5000°K	2400	A+
FPL-W04B-500	white	5500-6700°K	2400	A+
FPL-Y04B-500	yellow	590nm	200	E

the reduction of light output for IP64 products is about -10%, due to silicone is acting as a filter

Dimensions



Thickness: 3 mm +1
Thickness endings: 6.7 mm
DC-Power Jack: internal Ø 2.1 mm / external Ø: 5.5 mm

IP64: Protection against temporary immersion, no protection against UV, salt water/smog and chlorine not designed for submersion or outdoor usage IP protection is no longer applicable after cutting

1. All dimensions are in millimetres
2. Tolerance is ±0.50mm unless otherwise specified
3. Specifications are subject to change without notice

Please also take note of our **General Information for Flexiprint and LED Modules**