

Through hole LED

- high luminosity
- long lifetime up to 75'000 hours
- high quality for professional application
- RoHS compliant

∅ 5mm white



Part Number	Colour Temp. (°K)	Intensity (mcd)			Angle (deg)	Voltage (V)		Lens Colour	Type
		min	typ	max		typ	max		
L5-W55N-BVW	5500-9000	22000	31000	44000	15°	3.2	3.5	waterclear	1
L5-W53N-BVW	5500-9000	5200	7380	10400	45°	3.2	3.5	waterclear	2
L5-50N-BVW	5500-9000	1610	2320	3220	65°	3.2	3.5	white diffused	2

Electro-Optical-Characteristics Ta=25°C, Forward Current: IF Typical = 20mA,

1/10 Duty Cycle, 10ms Pulse Width: up to 110mA, depending on type number.


Storage Temp. -40 ~+100 (°C) Operating Temp. -30 ~+85 (°C)

Detailed data sheets are available on request

Packaging: 500pcs/bulk

Dimensions (mm)

Type	A	B	C	D	E
1	7.6	8.6	12.4	28.9	5.6
2	7.3	8.3	12.1	28.6	5.6



Sloan_04_GK_LED_14A

1. All dimensions are in millimetres
2. Tolerance is ±0.25mm unless otherwise specified
2. Specifications are subject to change without notice