

Flat indicator lights

Rotation-proof
Waterproof IP64 / IP67 / IP68

Flach-Leuchten

Verdrehsicher
Wasserdicht IP64 / IP67 / IP68

Voyants lumineux plats

Anti-rotation
Étanche IP64 / IP67 / IP68



3D Step-file
available on request



abgeflachte Seite = Kathode
flat side = cathode
côté plat = cathode




Series 343 / 344 / 348



3444S1G1G71NB



348811R1R50UB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“																				
Type / Typ / Type		Body / Körper / Corps			Accessories Zubehör Accessoires	Lens with.. Linse mit.. Lentille avec..		Light source Lichtquelle Source lum.		Voltage Spannung Tension										
Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface			Fresnel		LED Ø 5mm		Code	V	mA								
343		4	IP64	B	Brass, blackened Messing, geschwärzt Laiton, noirci	1		A1	Amber Orange Orange	Y54U 7'000 mcd	Yellow Gelb Jaune	0	series 343, only available without resistor	CL	29-48	20				
		7	IP67	S	Brass, nickel plated Messing, vernickelt Laiton, nickelé			B1	Blue Blau Bleu								Y50U 3'000 mcd			
		8	IP68	5	Stainless steel Edelstahl Acier inoxydable			C1	Clear Klar Clair								Y501 500 mcd			
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci			G1	Green Grün Vert	B91G 9'000 mcd	Blue Blau Bleu	constant current driver								
344				9	Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**	5		R1	Red Rot Rouge	B21G 2'120 mcd	Blue	CL1	5-28	20						
								W3	White Weiss Blanc	B61G 1'160 mcd										
																		Green Grün Vert	constant current driver	only for series 344, 348 and only for single colour
348		4	IP64	1	Brass, blackened Messing, geschwärzt Laiton, noirci	1		A1	Amber Orange Orange	R54U 7'000 mcd	Red Rot Rouge	other voltage and ranges on request.								
		7	IP67	2	Brass, nickel plated Messing, vernickelt Laiton, nickelé			B1	Blue Blau Bleu	R50U 3'000 mcd						R521 80 mcd				
		8	IP68	5	Stainless steel Edelstahl Acier inoxydable			5		C1	Clear Klar Claire	W55N 22'000 mcd				White Weiss Blanc				
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci					G1	Green Grün Vert	W50N 2'320 mcd								
				9	Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**					R1	Red Rot Rouge	RGKW common cathode only series 343, 348				Red-Green Rot-Grün Rouge-Vert				
										W3	White Weiss Blanc	RGVW common anode only series 343, 348								

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G“

Réserve de modifications de toutes les données techniques

34..

