



3D Step-file
available on request



134S10G301B

138S11010G301B

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires		Light source Lichtquelle Source lum.	Voltage Spannung Tension		
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface			LED Ø 3mm	Code	V	mA
134 	4 IP64	B Brass, blackened Messing, geschwärzt Laiton, noirci	1	0	Y33U 4'200 mcd Y30U 1'200 mcd Y301 30 mcd	Yellow Gelb Jaune	0	without ohne sans
	7 IP67	S Brass, nickel plated Messing, vernickelt Laiton, nickelé					A	5 20
	8 IP68						B	12 20
135 					B71G 6'220 mcd B41G 1'160 mcd	Blue Blau Bleu	D	24 20
					G41N 17'600 mcd G51N 10'320 mcd G301 40 mcd	Green Grün Vert	E	28 20
					R30U 5'500 mcd R301 8 mcd R33U 2'500 mcd	Red Rot Rouge		
Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lenght Länge Longueur				
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface						
138 	4 IP64	1 Brass, blackened Messing, geschwärzt Laiton, noirci	1	010	Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	W37N 13'350 mcd W36N 6'900 mcd W32N 3'745 mcd	White Weiss Blanc	
	7 IP67	2 Brass, nickel plated Messing, vernickelt Laiton, nickelé						
	8 IP68							

Operating Temperature: -30° to +85°C / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques