SLOAN
PRECISION OPTOELECTRONICS

Indicator lights with reflector
Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Reflektor
Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur
Anti-rotation
Option: étanche IP64 / IP67 / IP68

Series 333 / 334 / 338



3D Step-file
available on request



abgeflachte Seite = Kathode
flat side = cathode
côté plat = cathode



3348S1G501B




338821010Y501B

Further specifications and options in section „F-H" / Weitere Spezifikationen und Optionen in Kapitel „F-H" / Autres spécifications et options au chapitre „F-H"

Type / Typ / Type


Terminals
Anschlüsse
Raccords

333



LED terminals
LED-Anschlüsse
Fils des LEDs

334



Faston 2.8 x 0.5

Body / Körper / Corps

Protection Schutzart Protection		Surface Oberfläche Surface	
4	IP64	B	Brass, blackened Messing, geschwärzt Laiton, noirci
7	IP67	S	Brass, nickel plated Messing, vernickelt Laiton, nickelé
8	IP68	5	Stainless steel Edelstahl Acier inoxydable
		6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci
		9	Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**

Accessories Zubehör Accessoires

1	
5	Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305 

Light source Lichtquelle Source lum.

LED Ø 5mm

Y54U	7'000 mcd	Yellow Gelb Jaune
Y50U	3'000 mcd	
Y501	500 mcd	
B91G	9'000 mcd	Blue Blau Bleu
B21G	2'120 mcd	
B61G	1'160 mcd	
G81N	32'500 mcd	Green Grün Vert
G71N	6'500 mcd	
G501	250 mcd	
R54U	7'000 mcd	Red Rot Rouge
R50U	3'000 mcd	
R521	80 mcd	
W55N	22'000 mcd	White Weiss Blanc
W50N	2'320 mcd	
RGKW	common cathode only series 333, 338	Red-Green Rot-Grün Rouge-Vert
RGVW	common anode only series 333, 338	

Voltage Spannung Tension


Code	V	mA
0	without ohne sans	
series 333, only available without resistor		
CL	29-48	20
constant current driver only for series 334, 338 and only for single colour		
CL1	5-28	20
constant current driver only for series 334, 338 and only for single colour		
Z	230	2.5
only for series 338*		

other voltage and ranges on request.

Type / Typ / Type

Terminals
Anschlüsse
Raccords

338



Stranded wire
Litze
Fil multi-brins

Ø 0.14mm² (AWG 26)

Body / Körper / Corps

Protection Schutzart Protection		Surface Oberfläche Surface	
4	IP64	1	Brass, blackened Messing, geschwärzt Laiton, noirci
7	IP67	2	Brass, nickel plated Messing, vernickelt Laiton, nickelé
8	IP68	5	Stainless steel Edelstahl Acier inoxydable
		6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci
		9	Brass, olive darb** Messing, olivebraun** Laiton, olivebrun**

Accessories Zubehör Accessoires

1	
5	Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305 

Lenght Länge Longueur

010	Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G"

33..

SIBALCO AG • Birmannsgasse 8 • CH-4055 Basel • Tel. +41 (0)61 264 10 10 • Fax +41 (0)61 264 10 15 • info@sibalco.ch • www.sloan.ch