Indicator lights with reflector
Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Reflektor
Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur
Anti-rotation
Option: étanche IP64 / IP67 / IP68

Series 333 / 334 / 338

3D Step-file
available on request

3348S1G501B 338821010Y501B

B

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Terminals / Anschlüsse / Raccords	Body / Körper / Corps: Protection / Schutzart / Protection	Surface / Oberfläche / Surface	Accessories / Zubehör / Accessoires	Light source / Lichtquelle / Source lum. (LED Ø 5mm)	Voltage / Spannung / Tension: Code	V	mA
333	 LED terminals / LED-Anschlüsse / Fils des LEDs	**4** IP64	**B** Brass, blackened / Messing, geschwärzt / Laiton, noirci	**1**	**Y54U** 7'000 mcd Yellow / Gelb / Jaune	**0** without / ohne / sans		
		7 IP67	**S** Brass, nickel plated / Messing, vernickelt / Laiton, nickelé		**Y50U** 3'000 mcd	**A**	5	20
		8 IP68	**5** Stainless steel / Edelstahl / Acier inoxydable	**5** Stainless steel 1.4305 / Edelstahl 1.4305 / Acier inoxydable 1.4305	**Y501** 80 mcd	**B**	12	20
			6 Stainless steel, blackened / Edelstahl, geschwärzt / Acier inoxydable, noirci		**B91G** 9'000 mcd Blue / Blau / Bleu	**D**	24	20
			9 Brass, olive drab** / Messing, olivebraun** / Laiton, olivebrun**		**B21G** 2'120 mcd	**E**	28	20
334	 Faston 2.8 x 0.5				**B61G** 1'160 mcd	**CL** constant current driver; only for Series 334, 338 and only for single colour	9-48	20
					G81N 32'500 mcd Green / Grün / Vert			
					G71N 5'620 mcd	**CL1** constant current driver; only for Series 334, 338 and only for single colour	5-28	20
					G501 80 mcd			
					R54U 7'000 mcd Red / Rot / Rouge			
					R50U 3'000 mcd			
					R521 80 mcd	**Z** only for Series 338*	230	5
338	 Stranded wire / Litze / Fil multi-brins; Ø 0.14mm² (AWG 26)	**4** IP64	**1** Brass, blackened / Messing, geschwärzt / Laiton, noirci	**1**	**W55N** 22'000 mcd White / Weiss / Blanc			
		7 IP67	**2** Brass, nickel plated / Messing, vernickelt / Laiton, nickelé		**W50N** 2'320 mcd			
		8 IP68	**5** Stainless steel / Edelstahl / Acier inoxydable	**5** Stainless steel 1.4305 / Edelstahl 1.4305 / Acier inoxydable 1.4305	**RGKW** common cathode only series 333, 338 Red-Green / Rot-Grün / Rouge-Vert			
			6 Stainless steel, blackened / Edelstahl, geschwärzt / Acier inoxydable, noirci		**RGVW** common anode only series 333, 338			
			9 Brass, olive darb** / Messing, olivebraun** / Laiton, olivebrun**					

Lenght / Länge / Longueur	
010	Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

different LED's of the SLOAN range can be built in

RoHS compliant / ** except surface option 9 (none RoHS)

*refer to installation instructions for 230V version in chapter „G“

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

33..

Sloan_01_GK_Indicator-Lights_23A