

Indicator lights with reflector

Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Reflektor

Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur

Anti-rotation
Option: étanche IP64 / IP67 / IP68



3D Step-file
available on request






Series 353 / 354 / 358



354S1R521B

358811010Y501B

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“																
Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires		Light source Lichtquelle Source lum.		Voltage Spannung Tension								
Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface			LED Ø 5mm		Code	V mA							
353		4	IP64	B	Brass, blackened Messing, geschwärzt Laiton, noirci	1		Y54U 7'000 mcd Yellow Gelb Jaune	0	without ohne sans						
		7	IP67	S	Brass, nickel plated Messing, vernickelt Laiton, nickelé					A	5 20					
		8	IP68	5	Stainless steel Edelstahl Acier inoxydable				5	Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305	B	12 20				
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci						D	24 20				
354				9	Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**			B21G 2'120 mcd Blue Blau Bleu	E	28 20						
									B61G 1'160 mcd	CL	9-48 20					
									G81N 32'500 mcd Green Grün Vert	G71N 6'500 mcd G501 80 mcd	CL1	5-28 20				
													R54U 7'000 mcd Red Rot Rouge	R50U 3'000 mcd R521 80 mcd	only for series 354, 358 and only for single colour	
Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires		Lenght Länge Longueur											
	Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface												
	358		4	IP64	1	Brass, blackened Messing, geschwärzt Laiton, noirci	1		010	Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	W55N 22'000 mcd White Weiss Blanc					
			7	IP67	2	Brass, nickel plated Messing, vernickelt Laiton, nickelé									W50N 2'320 mcd	
8			IP68	5	Stainless steel Edelstahl Acier inoxydable	5								Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305	RGKW common cathode only series 353, 358	Red-Green Rot-Grün Rouge-Vert
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci											
				9	Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**											

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G“

Réserve de modifications de toutes les données techniques

35..

