

Indicator lights
 Mounting diameter \varnothing 14mm
 Waterproof IP65

Signalleuchten
 Montageloch \varnothing 14mm
 Wasserdicht IP65

Voyants Lumineux
 Trou de montage \varnothing 14mm
 Étanche IP65



3D Step-file
 available on request



941YY0B

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Colour cap Farbkappe Capuchon de couleur	Light source Lichtquelle Source lum.	Voltage Spannung Tension				
	Surface Oberfläche Surface	Protection Schutzart Protection				Code	V	mA		
941 Screw terminals Schraubanschlüsse Contact à vis All versions also available as flashing units. Put a "F" for flashing at the end of the part-no. Alle Versionen auch blinkend erhältlich. Ergänzen Sie ein „F“ am Ende der Artikel-Nr. Version clignotante possible pour tous les modèles. Ajouter la lettre "F" à la fin du numéro d'article.	Material: ABS Black Material: ABS Schwarz Matériel: ABS Noir	IP65	Nut & O-Ring Mutter & O-Ring Ecrou & Joint 	B Blue Blau Bleu	BO 1 LED 3'000mcd 470nm	Blue Blau Bleu	B 12V AC/DC	20		
				G Green Grün Vert	GO 1 LED 3'000mcd 565nm	Green Grün Vert			D 24V AC/DC	
				R Red Rot Rouge	RO 1 LED 800mcd 660nm	Red Rot Rouge				Z 230V AC
				W White Weiss Blanc	WO 1 LED 1'200mcd 6'500K	White Weiss Blanc				
				Y Yellow Gelb Jaune	YO 1 LED 1'200mcd 585nm	Yellow Gelb Jaune				

Operating Temperature: -25° to +55°C / Storage Temperature: -20° to +50°C

RoHS compliant

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

941

