

Indicator lights
Mounting diameter ø22mm
Waterproof IP65

Signalleuchten
Montageloch ø22mm
Wasserdicht IP65

Voyants Lumineux
Trou de montage ø22mm
Étanche IP65

Series 951



3D Step-file
available on request



951RROB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

| Type / Typ / Type | Body / Körper / Corps | | Accessories Zubehör Accessoires | Colour cap Farbkappe Capuchon de couleur | Light source Lichtquelle Source lum. | | Voltage Spannung Tension | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------|----------------------------------------------------------|------------------------------------------------|--------------------------------------------|-------------------------|--------------------------------|--------------|----|
| | Surface Oberfläche Surface | Protection Schutzart Protection | | | Code | V | mA | | |
| 951 Screw terminals Schraubanschlüsse Contact à vis All versions also available as flashing units. Put a "F" for flashing at the end of the part-no. Alle Versionen auch blinkend erhältlich. Ergänzen Sie ein „F“ am Ende der Artikel-Nr. Version clignotante possible pour tous les modèles. Ajouter la lettre "F" à la fin du numéro d'article. | Material: ABS Black Material: ABS Schwarz Matériel: ABS Noir | IP65 | Nut & O-Ring Mutter & O-Ring Ecrou & Joint | B Blue Blau Bleu | B3 4 LEDs 4'800mcd 470nm | Blue Blau Bleu | B | 12V AC/DC | 20 |
| | | | | G Green Grün Vert | G0 4 LEDs 800mcd 565nm | Green Grün Vert | D | 24V AC/DC | 20 |
| | | | | | G3 4 LEDs 21'000mcd 525nm | Red Rot Rouge | J | 48V AC/DC | 10 |
| | | | | R Red Rot Rouge | R0 4 LEDs 3'000mcd 660nm | White Weiss Blanc | X | 115V AC | 5 |
| | | | | W White Weiss Blanc | W3 4 LEDs 22'000mcd 6'500K | Yellow Gelb Jaune | Z | 230V AC | 20 |
| | | | | Y Yellow Gelb Jaune | Y0 4 LEDs 250mcd 585nm | Yellow Gelb Jaune | | | |
| | | | | | Y3 4 LEDs 8'700mcd 590nm | Yellow Gelb Jaune | | | |

Operating Temperature -25° to +55°C / Storage Temperature: -20° to +50°C

RoHS compliant

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

951

