

**Indicator lights**  
 Mounting diameter ø22mm  
 Waterproof IP65

**Signalleuchten**  
 Montageloch ø22mm  
 Wasserdicht IP65

**Voyants Lumineux**  
 Trou de montage ø22mm  
 Étanche IP65



3D Step-file  
 available on request



956BB0B

**Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“**

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Colour cap Farbkappe Capuchon de couleur	Light source Lichtquelle Source lum.	Voltage Spannung Tension				
	Surface Oberfläche Surface	Protection Schutzart Protection				Code	V	mA		
<b>956</b>  Screw terminals Schraubanschlüsse Contact à vis  All versions also available as flashing units. Put a "F" for flashing at the end of the part-no.  Alle Versionen auch blinkend erhältlich. Ergänzen Sie ein „F“ am Ende der Artikel-Nr.  Version clignotante possible pour tous les modèles. Ajouter la lettre "F" à la fin du numéro d'article.	Material: ABS Black Material: ABS Schwarz Matériel: ABS Noir	IP65	Nut & O-Ring Mutter & O-Ring Ecrou & Joint 	<b>B</b> Blue Blau Bleu	<b>B0</b> 1 LED 3'000mcd 470nm	Blue Blau Bleu	<b>B</b> 12V AC/DC	20		
				<b>G</b> Green Grün Vert	<b>G0</b> 1 LED 3'000mcd 565nm	Green Grün Vert			<b>D</b> 24V AC/DC	
				<b>R</b> Red Rot Rouge	<b>R0</b> 1 LED 800mcd 660nm	Red Rot Rouge				<b>Z</b> 230V AC
				<b>W</b> White Weiss Blanc	<b>W0</b> 1 LED 1'000mcd 6'500K	White Weiss Blanc				
				<b>Y</b> Yellow Gelb Jaune	<b>Y0</b> 1 LED 800mcd 585nm	Yellow Gelb Jaune				

Operating Temperature -25° to +55°C / Storage Temperature: -20° to +50°C

RoHS compliant

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

**956**

