

Indicator lights with colour cap


Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Farbkappen

Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec capuchon

Anti-rotation
Option: étanche IP64 / IP67 / IP68



3D Step-file
available on request



Series 117 / 119



1174S11R1R30UB

119411G1G51NB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Colour caps with.. Farbkappen mit.. Capuchons encreurs avec..		Light source Lichtquelle Source lum.	Voltage Spannung Tension						
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface			Fresnel	LED Ø 3mm	Code	V	mA				
117 Solder lugs Lötösen Contact à souder	4 IP64	B Brass, blackened Messing, geschwärzt Laiton, noirci	1 	1 cylindrical zylindrisch cylindrique 6 domed gewölbt dôme 	A1 Amber Orange Orange	Y33U 4'200 mcd	0	without ohne sans					
	7 IP67	S Brass, nickel plated Messing, vernickelt Laiton, nickelé			B1 Blue Blau Bleu	Y30U 1'200 mcd				A	5	20	
	8 IP68	9 Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**			C1 Clear Klar Clair	Y301 30 mcd				B	12	20	
						G1 Green Grün Vert	B71G 6'220 mcd	D	24	20			
						R1 Red Rot Rouge	B41G 1'160 mcd				E	28	20
						W3 White Weiss Blanc							
						G41N 17'600 mcd G51N 10'320 mcd G301 40 mcd	Green Grün Vert						
								R30U 5'500 mcd R301 8 mcd R33U 2'500 mcd	Red Rot Rouge				
								W37N 13'350 mcd W36N 6'900 mcd W32N 3'745 mcd	White Weiss Blanc				
	119 Stranded wire Litze Fil multi-brins Ø 0.14mm² (AWG 26) Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	4 IP64			1 Brass, blackened Messing, geschwärzt Laiton, noircie				R301 8 mcd R33U 2'500 mcd	0			
7 IP67		2 Brass, nickel plated Messing, vernickelt Laiton, nickelée			A			5	20				
8 IP68		9 Brass, olive darb** Messing, olivebraun** Laiton, olivebrun**			B			12	20				
					D			24	20				
					E			28	20				

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

11..



1

