

Indicator lights with colour cap


Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Farbkappen

Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec capuchon

Anti-rotation
Option: étanche IP64 / IP67 / IP68



3D Step-file
available on request



abgeflachte Seite = Kathode
flat side = cathode
côté plat = cathode



1781816A1Y50UB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps	Accessories Zubehör Accessoires	Colour caps with.. Farbkappen mit.. Capuchons encreurs avec..	Light source Lichtquelle Source lum.	Voltage Spannung Tension
Terminals Anschlüsse Raccords	Surface Oberfläche Surface	Protection Schutzart Protection		LED Ø 5mm	Code V mA
174	B Brass, blackened Messing, geschwärzt Laiton, noirci S Brass, nickel plated Messing, vernickelt Laiton, nickelé 5 Stainless steel Edelstahl Acier inoxydable 6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci 9 Brass, olive drab** Messing, olivbraun** Laiton, olivbrun**	4 IP64 7 IP67 8 IP68	1  6  5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305  	Y54U 7'000 mcd Y50U 3'000 mcd Y501 500 mcd B91G 9'000 mcd B21G 2'120 mcd B61G 1'160 mcd G81N 32'500 mcd G71N 6'500 mcd G501 250 mcd R54U 7'000 mcd R50U 3'000 mcd R521 80 mcd	0 without ohne sans series 177 is only available without resistor CL constant current driver only for Series 174, 178 and only for single colour CL1 constant current driver only for Series 174, 178 and only for single colour Z 230 2.5 only for Series 178* other voltage and ranges on request.
177	1 Brass, blackened Messing, geschwärzt Laiton, noirci 2 Brass, nickel plated Messing, vernickelt Laiton, nickelé 5 Stainless steel Edelstahl Acier inoxydable 6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci 9 Brass, olive drab** Messing, olivbraun** Laiton, olivbrun**	4 IP64 7 IP67 8 IP68	1  6  5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305  	A1 Amber Orange B1 Blue Blau Bleu C1 Clear Klar Clair G1 Green Grün Vert R1 Red Rot Rouge W3 White Weiss Blanc	W55N 22'000 mcd W50N 2'320 mcd RGKW common cathode only series 177, 178 RGVW common anode only series 177, 178
178	1 Brass, blackened Messing, geschwärzt Laiton, noirci 2 Brass, nickel plated Messing, vernickelt Laiton, nickelé 5 Stainless steel Edelstahl Acier inoxydable 6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci 9 Brass, olive drab** Messing, olivbraun** Laiton, olivbrun**	4 IP64 7 IP67 8 IP68	1  6  5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305  	A1 Amber Orange B1 Blue Blau Bleu C1 Clear Klar Clair G1 Green Grün Vert R1 Red Rot Rouge W3 White Weiss Blanc	W55N 22'000 mcd W50N 2'320 mcd RGKW common cathode only series 177, 178 RGVW common anode only series 177, 178

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G“

Réserve de modifications de toutes les données techniques

17..

