

## Indicator lights with colour cap

Rotation-proof  
Option: waterproof IP64 / IP67 / IP68

## Signalleuchten mit Farbkappen

Verdrehsicher  
Option: wasserdicht IP64 / IP67 / IP68

## Voyants lumineux avec capuchon

Anti-rotation  
Option: étanche IP64 / IP67 / IP68



3D Step-file  
available on request



## Series 174 / 177 / 178



174S811R1R50UB

1781816A1Y50UB

### Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Colour caps with.. Farbkappen mit.. Capuchons encreurs avec..		Light source Lichtquelle Source lum.		Voltage Spannung Tension							
	Surface Oberfläche Surface	Protection Schutzart Protection		Fresnel		LED Ø 5mm	Code	V	mA						
<b>174</b>  Faston 2.8 x 0.5	<b>B</b>	Brass, blackened Messing, geschwärzt Laiton, noirce	<b>4</b>	IP64	<b>1</b>		<b>1</b>	cylindrical zylindrisch cylindrique	<b>A1</b>	Amber Orange Orange	<b>Y54U</b> 7'000 mcd	Yellow Gelb Jaune	<b>0</b>	without ohne sans	
	<b>S</b>	Brass, nickel plated Messing, vernickelt Laiton, nickelée	<b>7</b>	IP67	<b>1</b>		<b>1</b>		<b>B1</b>	Blue Blau Bleu	<b>Y50U</b> 3'000 mcd		<b>A</b>	5	20
	<b>5</b>	Stainless steel Edelstahl Acier inoxydable	<b>8</b>	IP68	<b>5</b>	Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305	<b>6</b>	domed gewölbt dôme	<b>C1</b>	Clear Klar Claire	<b>Y501</b> 80 mcd		<b>B</b>	12	20
	<b>9</b>	Brass, olive drab** Messing, olivbraun** Laiton, olivebrun**							<b>G1</b>	Green Grün Vert	<b>B91G</b> 9'000 mcd	Blue Blau Bleu	<b>D</b>	24	20
<b>177</b>  LED terminals LED-Anschlüsse Fils des LEDs									<b>R1</b>	Red Rot Rouge	<b>B21G</b> 2'120 mcd		<b>E</b>	28	20
									<b>W3</b>	White Weiss Blanc	<b>B61G</b> 1'160 mcd		<b>CL</b>	9-48	20
											<b>G81N</b> 32'500 mcd	Green Grün Vert			
											<b>G71N</b> 5'620 mcd				
<b>178</b>  Stranded wire Litze Fil multi-brins Ø 0.14mm² (AWG 26)										<b>R54U</b> 7'000 mcd	Red Rot Rouge				
										<b>R50U</b> 3'000 mcd					
										<b>R521</b> 80 mcd			<b>Z</b>	230	5
											<b>W55N</b> 22'000 mcd	White Weiss Blanc			
										<b>W50N</b> 2'320 mcd					
										<b>RGVW</b> common anode only series 343, 348	Red-Green Rot-Grün Rouge-Vert				
										<b>G1</b>	Green Grün Vert				
										<b>R1</b>	Red Rot Rouge				
										<b>W3</b>	White Weiss Blanc				

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / \*\* except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

17..

