

## Indicator lights with colour cap

Rotation-proof  
Option: waterproof IP64 / IP67 / IP68

## Signalleuchten mit Farbkappen

Verdrehsicher  
Option: wasserdicht IP64 / IP67 / IP68

## Voyants lumineux avec capuchon

Anti-rotation  
Option: étanche IP64 / IP67 / IP68



3D Step-file  
available on request



1781816A1Y50UB

### Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Colour caps with.. Farbkappen mit.. Capuchons encreurs avec..		Light source Lichtquelle Source lum.	Voltage Spannung Tension										
	Surface Oberfläche Surface	Protection Schutzart Protection		Fresnel	LED Ø 5mm		Code	V	mA								
<b>174</b>  Faston 2.8 x 0.5	<b>B</b> Brass, blackened Messing, geschwärzt Laiton, noirci	<b>4</b> IP64	<b>1</b>	<b>6</b> domed gewölbt dôme	<b>A1</b> Amber Orange Orange	<b>Y54U</b> 7'000 mcd	Yellow Gelb Jaune	<b>0</b>	without ohne sans								
	<b>S</b> Brass, nickel plated Messing, vernickelt Laiton, nickelé	<b>7</b> IP67	<b>2</b>		<b>B1</b> Blue Blau Bleu	<b>Y50U</b> 3'000 mcd				<b>A</b>	5	20					
	<b>5</b> Stainless steel Edelstahl Acier inoxydable	<b>8</b> IP68	<b>5</b> Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305 		<b>C1</b> Clear Klar Clair	<b>Y501</b> 500 mcd					<b>B</b>	12	20				
	<b>6</b> Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci				<b>G1</b> Green Grün Vert	<b>B91G</b> 9'000 mcd						Blue Blau Bleu	<b>D</b>	24	20		
	<b>9</b> Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**				<b>R1</b> Red Rot Rouge	<b>B21G</b> 2'120 mcd								<b>E</b>	28	20	
	<b>W3</b> White Weiss Blanc	<b>B61G</b> 1'160 mcd	<b>CL</b>	9-48	20												
<b>177</b>  LED terminals LED-Anschlüsse Fils des LEDs					<b>G81N</b> 32'500 mcd	Green Grün Vert	constant current driver only for Series 174, 178 and only for single colour	<b>CL1</b>	5-28	20							
											<b>G71N</b> 6'500 mcd				<b>G501</b> 250 mcd	<b>Z</b>	230
											<b>R54U</b> 7'000 mcd	Red Rot Rouge	only for Series 174, 178 and only for single colour				
											<b>R50U</b> 3'000 mcd						
					<b>R521</b> 80 mcd												
				<b>W55N</b> 22'000 mcd	White Weiss Blanc	only for Series 178*											
				<b>W50N</b> 2'320 mcd													
				<b>RGKW</b> common cathode only series 177, 178			Red-Green Rot-Grün Rouge-Vert										
				<b>RGVW</b> common anode only series 177, 178													
				<b>R1</b> Red Rot Rouge													
				<b>W3</b> White Weiss Blanc													
<b>178</b>  Stranded wire Litze Fil multi-brins Ø 0.14mm² (AWG 26)	<b>1</b> Brass, blackened Messing, geschwärzt Laiton, noirci	<b>4</b> IP64	<b>1</b>	<b>6</b> domed gewölbt dôme	<b>A1</b> Amber Orange Orange	<b>W55N</b> 22'000 mcd	White Weiss Blanc	<b>Z</b>	230	2.5							
	<b>2</b> Brass, nickel plated Messing, vernickelt Laiton, nickelé	<b>7</b> IP67	<b>2</b>		<b>B1</b> Blue Blau Bleu	<b>W50N</b> 2'320 mcd											
	<b>5</b> Stainless steel Edelstahl Acier inoxydable	<b>8</b> IP68	<b>5</b> Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305 		<b>C1</b> Clear Klar Clair	<b>RGKW</b> common cathode only series 177, 178					Red-Green Rot-Grün Rouge-Vert						
	<b>6</b> Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci				<b>G1</b> Green Grün Vert	<b>RGVW</b> common anode only series 177, 178											
	<b>9</b> Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**				<b>R1</b> Red Rot Rouge												
				<b>W3</b> White Weiss Blanc													

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / \*\* except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

17..

