

Flexiprint IP20

3528 PLCC2, single colour, standard bright

FP1-x01D-500

Specifications

Voltage	24V
Current	1A
Wattage	4.8W/m
Number of LEDs	300pcs
Length of stripe	5m
Viewing angle	120°
Min. bending radius (edges/corners)	30mm
Operating temperature	-15 to +40°C
Storage temperature	-25 to +60°C
CE/RoHS compliant	




Benefits

Adhesive tape on backside
Cuttable every ~100mm


Electrical and optical characteristics (Ta=25°C)

Part number	Colour	Wavelength	Intensity lm/m	
FP1-B01D-500	 blue	470nm	66	
FP1-G01D-500	 green	520nm	283	
Part number	Colour	CCT	Intensity lm/m	EEC
FP1-H01D-500	 warm-white	2600-2800°K	420	G
FP1-N01D-500	 warm-white	2800-3500°K	468	F
FP1-S01D-500	 natural-white	3800-5000°K	498	F
FP1-W01D-500	 cold-white	5500-7000°K	498	F

Dimensions



Additional



Quick connector for a solderless connection with the LED stripe.
Part-no.: SLO-C310-00001
(details on page 36)

1. All dimensions are in millimetres
2. Length tolerance $\pm 1\%$
3. All strandet wires cross section 0.2mm² AWG #24
4. Specifications are subject to change without notice

Please also take note of our **General Information for Flexiprint and LED Modules**