

THT LED

Ø 5mm blue

- high luminosity
- long lifetime up to 75'000 hours
- high quality for professional application
- RoHS compliant



Part Number	Old Part Number	Peak Wavelength	Intensity (mcd)			Angle (deg)	Voltage (V)		Lens Colour	Type
			min	typ	max		typ	max		
SLO-234B-00010	L5-B91G-WUV	● 465nm	4880	9300	13950	15°	3.2	3.5	waterclear	1
SLO-234B-00005	L5-B21G-WVV	● 475nm	3010	4700	6020	30°	3.2	3.5	waterclear	2
SLO-234B-00007	L5-B5SC	● 480nm	1000	2500	4000	30°	3.5	3.8	waterclear	3

Electro-Optical-Characteristics Ta=25°C, Forward Current: IF Typical = 20mA,

1/10 Duty Cycle, 10ms Pulse Width: up to 110mA, depending on type number.


Storage Temp. -40 ~+100 (°C) Operating Temp. -30 ~+85 (°C)

Detailed data sheets are available on request

Packaging: 500pcs/bulk

Dimensions (mm)

Type 1 - 3



Type	A	B	C	D	E
1	7.6	8.6	12.4	28.9	5.6
2	7.3	8.3	12.1	28.6	5.6
3	7.6	8.6	NA	34.1	5.8